

# Electric Vehicle Charging Infrastructure

## Terra multi-standard DC charging station 53

The Terra multi-standard DC charging station 53 is a configurable single, dual or triple outlet 50 kW fast charging station. Its flexible multi-protocol design supports CCS, CHAdeMO and AC functionality depending on the individual charging needs of each customer. Designed for en route charging, the Terra 53 is ideal for use at car dealerships, petrol stations and busy urban areas.



The Terra multi-standard DC charging station 53 combines industry standardization with fast charging technology to support all current and next generation vehicles. Its multi-protocol design allows for easy tailoring to support CCS and CHAdeMO 1.0 for DC fast charging, as well as the EN61851-1 standard for AC charging (type 2, mode 3).

All ABB chargers come with Internet based Connected services to allow customers to easily connect their chargers to different software systems like back-offices, payment platforms or smart grid energy systems. This allows for remote assistance, tailored diagnostic trouble shooting and repair, and remote updates and upgrades. A reliable, secure, cost efficient and future proof connectivity solution, based on open industry interfaces.

### Main features

- CCS standard DC fast charging
  - 30 to 80% of a 24 kW battery in 15 minutes
- Future proof connection via open industry standards
  - Flexible interfacing with added value systems
  - Remote uptime monitoring and assistance
  - Remote updates and upgrades
- Easy to use
  - 8" daylight readable touch screen display
  - Graphic visualisation of charging progress
  - RFID authorization
- Aesthetic all weather stainless steel enclosure
- Quick and easy installation
- Low operational noise

### Applications

- Highway petrol/service station operators
- Busy urban areas
- Commercial fleet operators
- EV Infrastructure operators and service providers
- CCS EV dealers and importers

### Key optional features

- CHAdeMO 1.0 DC fast charging expansion package
- AC fast charging expansion package (T or G)
  - 22 kW AC socket (T) or 43 kW AC connector (G)
- Simultaneous AC and DC charging
- Option: Remote resettable MCB and RCD to maximize uptimes
- Pin code authorization
- Input power limiting software to avoid expensive grid upgrades
- Web modules for statistics and access management
- Integration with back-offices, payment platforms and smart grid energy systems
- Wider temperature range: -35°C to +50°C
- Customized branding possibilities

### Possible configurations

The Terra 53 is available in several configurations: C, CT (CCS and AC socket), CJ (CCS and CHAdeMO) and CJG (CCS, CHAdeMO and AC connector)

Outlet specifications	C (default)	J (option)	G (option)	T (option)
Charging standard	CCS	CHAdeMO	Type 2 cable	Type 2 socket
Maximum output power	50 kW	50 kW	43 kW	22 kW
Output voltage range	50 - 500 V <sub>DC</sub>	50 - 500 V <sub>DC</sub>	400 V +/- 10%	400 V +/- 10%
Maximum output current	125 A <sub>DC</sub>	125 A <sub>DC</sub>	63 A	32 A
Connection standard	EN61851-23 / DIN 70121	CHAdeMO 1.0	EN61851-1:2010	EN61851-1:2010
Connector/socket type	Combo-2	CHAdeMO / JEVS G105	IEC62196 mode-3 type-2	IEC62196 mode-3 type 2
Cable length	3,9 m	3,9 m	3,9 m	-
Compatible car brands	BMW, Volkswagen, GM, Porsche, Audi	Nissan, Mitsubishi, Peugeot, Citroen, Kia	Renault, Daimler, Tesla, Smart, Mercedes	Renault, Daimler, Tesla, Smart, Mercedes, Volvo, Opel




Possible configurations (from left to right): Terra 53 C, Terra 53 CT, Terra 53 CJ, Terra 53 CJG

#### General specifications


Environment	Indoor / outdoor
Operating temperature	-10 °C to +50 °C (de-rating characteristic applies) Option: -35 °C to +50 °C
Storage temperature	-40 °C to +70 °C
Compliance and safety	CE / Option: CHAdeMO
Input AC power connection	3P + N + PE
Input voltage range	400 V <sub>AC</sub> +/- 10% (50 Hz or 60 Hz)
Max. rated input current & power	C, CJ: 80 A, 55 kVA CT: 112 A, 77 kVA CJG: 143 A, 98 kVA Power limiting options available
Power factor (full load)	> 0.96
Efficiency	94% at nominal output power
RFID system	ISO/IEC14443A/B, ISO/IEC15693, FeliCa™ 1, NFC reader mode, LEGIC Prime & Advant
Network connection	GSM / CDMA / 3G modem, 10/100 Base-T Ethernet
Protection	IP54
Dimensions (D x W x H)	760 mm x 525 mm x 1900 mm
Mass	400 kg

#### Advantages of connected charging


Flexible interfacing with customer's added value systems




Optimal insight in charger operation



Maximize charger uptime with fast and reliable service



Optimize user experience



For more information please contact:

#### ABB EV Charging Infrastructure

Delftweg 65  
2289 BA Rijswijk  
The Netherlands  
Phone: +31 70 307 6200  
Fax: +31 70 307 6209

[www.abb.com/evcharging](http://www.abb.com/evcharging)

Power and productivity  
for a better world™

